


# Ka-BAND LOW NOISE BLOCK

## ACLNBW-Ka-E33-V3

Wideband Series Simultaneous Outputs

The ACLNB-Ka family of LNBs is designed for the most challenging Ka-band professional & military satellite communication systems (ground, SOTP, SOTM, maritime, etc.). Latest technology is applied to obtain the best noise figure, phase noise, gain stability and return losses according to MIL-STD-188-164C. The ACLNB-Ka family is a high reliability solution designed for harsh environmental conditions, with every single production unit fully tested in an environmental chamber and delivered with a complete factory acceptance test report.



### RECEIVER SPECIFICATIONS

|                                 |                                              |
|---------------------------------|----------------------------------------------|
| Input frequency                 | 17.7 to 21.2 GHz                             |
| Input Ka-Band VSWR (50 Ω)       | < 1.5:1                                      |
| Output frequency                | 1000 to 2000 MHz                             |
| Output L-band VSWR (50 Ω)       | < 2.0:1                                      |
| Spectrum inversion              | None                                         |
| Max. input level without damage | 0 dBm                                        |
| Gain                            | 60 dB min                                    |
| Gain flatness                   | ±2.0 dB over whole BW<br>±0.5 dB over 40 MHz |
| Gain stability (24 hours)       | ±0.25 dB @ const. temp.                      |
| Gain variation over temperature | ±1.5 dB (±2.0 dB option LN2)                 |
| Noise figure @ 25 °C            | ≤ 1.8 dB                                     |
| Noise temperature @ 25 °C       | ≤ 150 K                                      |
| Image rejection                 | > 40 dB                                      |
| Output P1dB                     | > +10 dBm                                    |
| In-band spurious                | < -60 dBc @ P <sub>OUT</sub> = 0 dBm         |

### LOCAL OSCILLATOR

Output phase noise (IESS-308/309 - 5 dB)

|                              |                     |
|------------------------------|---------------------|
| 100 Hz                       | -65 dBc/HZ          |
| 1 kHz                        | -75 dBc/HZ          |
| 10 kHz                       | -85 dBc/HZ          |
| 100 kHz                      | -95 dBc/HZ          |
| External reference           | 10 MHz              |
| External reference level     | 0 dBm ± 5 dB        |
| Internal reference stability | ±1 ppm (option LN3) |

### POWER SUPPLY

|                      |                                            |
|----------------------|--------------------------------------------|
| DC input voltage     | 12-24 Vdc                                  |
| Consumption @ 24 Vdc | 560 mA typ<br>(140 mA typ per output port) |

### MECHANICAL SPECIFICATIONS

|              |                                         |
|--------------|-----------------------------------------|
| Size (LxWxH) | 140 x 155 x 40 mm<br>5.6 x 6.1 x 1.6 in |
| Weight       | 950 g<br>2.1 lbs                        |
| Finish       | RAL 9003 (White)                        |

### ENVIRONMENTAL SPECIFICATIONS

|                       |                  |
|-----------------------|------------------|
| Storage temperature   | -40 °C to +85 °C |
| Operating temperature | -20 °C to +60 °C |
| Relative humidity     | up to 100%       |
| Operating altitude    | up to 4500 m     |

### INTERFACES

|                                  |                        |
|----------------------------------|------------------------|
| RX input (Ka-Band)               | WR42 grooved (PBR 220) |
| RX output 1 (L-Band+DC+Ext.Ref.) | Type N(F) 50 Ω         |
| RX output 2 (L-Band+DC+Ext.Ref.) | Type N(F) 50 Ω         |
| RX output 3 (L-Band+DC+Ext.Ref.) | Type N(F) 50 Ω         |
| RX output 4 (L-Band+DC+Ext.Ref.) | Type N(F) 50 Ω         |

### OPTIONS

| Ka-band input                                                                |                  | L-band output                                                                |
|------------------------------------------------------------------------------|------------------|------------------------------------------------------------------------------|
| 17.7 to 18.2 GHz<br>18.2 to 19.2 GHz<br>19.2 to 20.2 GHz<br>20.2 to 21.2 GHz |                  | 1000 to 1500 MHz<br>1000 to 2000 MHz<br>1000 to 2000 MHz<br>1000 to 2000 MHz |
| LO freq.                                                                     | Output port      | Standard freq. option                                                        |
| 16.7 GHz<br>17.2 GHz<br>18.2 GHz<br>19.2 GHz                                 | 1<br>2<br>3<br>4 | ACLNBW-Ka-E33-V3                                                             |

|     |                                        |
|-----|----------------------------------------|
| LN1 | RX output connector type SMA(F) 50 Ω   |
| LN2 | Operating temperature -40 °C to +60 °C |
| LN3 | Internal reference ACLNBW-I-Ka-E33-V3  |
| LN4 | Supply and ext. ref. over single port  |

