

FLYAWAY ANTENNA ASL 1.8 MPA Ku, X, C Band

Carbon Fiber Manual Antenna



Features:

- High strength, light weight, carbon fiber *reflector with a surface accuracy of $<0.3\text{mm RMS}$.
- Easy assembly and operation, without training or tools.
- Azimuth & elevation angle adjustment realizes fast and fine tuning functions, it rapidly decreases the satellite acquisition period.
- Supports C, X, Ku and Ka-band operation.
- Supports various requirements such as, Broadcast & Media, Emergency & Public Safety, Oil & Gas, etc.

Antenna System Specification

RF Feature				
Reflector Aperture	1.8m			
Reflector Material	Carbon Fiber			
Reflector Type	Offset			
Tx Frequency(GHz)	13.75~14.5	7.9~8.4	5.85~6.725	5.85~6.425
Rx Frequency(GHz)	10.95~12.75	7.25~7.75	3.40~4.20	3.625~4.20
Tx Gain(dBi)	46.3+20 lg(f/14.25)	41.5+20 lg(f/8.2)	39.3+20 lg(f/6.25)	38.7
Rx Gain(dBi)	45.3+20 lg(f/12.5)	40.8+20 lg(f/7.5)	35.4+20 lg(f/3.8)	35.4
Tx Isolation	>85dB	>85dB	>85dB	
Rx Isolation	>35dB	>35dB	>35dB	
Polarization Feature	Linear	Circular	Linear	Circular
G/T (dB/K)	24.4 (20° EL)	18.8 (10° EL. 50k NA)		
Feed Interface	WR75	WR112	Tx WR137 Rx WR229	Tx WR137 Rx WR229
Side Lobe	first side lobe < -14 dB 29-25logθ (1° ≤θ <20°) 32-25logθ (20° ≤θ <48°) -10 dB (θ ≥48°)			
Cross Polarization	≥35 dB (Axis) ≥30dB(-1dB)			
Mechanical Feature				
Case Contents	Rotary Table	Side:1260*550*650mm		Weight: 60Kg
	Support Leg	Side:1570*580*420mm		Weight: 58Kg
Slewing area	Azimuth	± 180°		
	Elevation	10°~90°		
	Polarization	± 95°		± 95°
Operational Wind	30km/h (8mps) Random 72km/h (20mps) With anchored unit			
Temperature	-40° C to +60° C			
Pointing Loss	Maximum 2.0 dB peak Rx loss at Ku			
Humidity	98%			