



EUROSATCOM
VSATECH ASSOCIÉ

LNB C-BAND EXT REF 3000X

SPECIFICATIONS

Noise Temperature at room temp. @CF	20K: 20K typ., 24K Max. 25K: 25K typ., 28K Max. 30K: 30K typ., 32K Max.
L.O. Stability	Phase Locked to External Reference
Phase noise (SSB) max.	Depends on External Reference
Input VSWR	2.5 : 1 max.
Output VSWR	2.5 : 1 max.
Gain	65 dB typ., 60 dB min., 70 dB max.
Gain Flatness (over full band)	≤ 4 dB p-p max.
Output P1dB	+ 3 dBm min.
DC Power	+ 12V to + 24 V DC
Current	250 mA max.
Input (waterproof)	CPR-229G waveguide grooved
Output (waterproof)	F-Connector (75 Ohm) N-Connector (50 Ohm)
Dimensions (L x W x H)	180 mm x 100 mm x 70 mm (7.1 in x 4.0 in x 2.8 in)
Weight	575 g (20.28 oz)




Operating Temperature	- 40 to + 60°C
Storage Temperature	- 40 to + 80°C
External Ref. Freq.	10 MHz (sine-wave), -5 to +5 dBm

FREQUENCY BANDS

Frequency Band (GHz)	3.40 to 4.20
L.O. Frequency (GHz)	5.15
IF Frequency (MHz)	950 to 1750

MECHANICAL DIAGRAM



HOW TO ORDER

3025XN

CONNECTOR
F - 75 Ohm
N - 50 Ohm

EXTERNAL REFERENCE

NOISE TEMPERATURE
20 - 20K
25 - 25 K
30 - 30 K

LNB SERIES #



EUROSATCOM
VSATECH ASSOCIÉ

3 avenue du Canada, bât. Zeta, 91940 Les Ulis, France

+33 1 69 18 19 30

www.eurosatcom.eu

sales@eurosatcom.eu